



STANDARD FIRM
STITCHBONDED
POLYESTER FABRIC

STANDARD FIRM STITCHBONDED POLYESTER FABRIC

E-las•tek Standard Firm (Tietex T-326) is a 2.70-ounce stitchbonded style polyester fabric with a firm finish used in the reinforcement of cold-process roofing systems. It is also used as a flashing reinforcement with mastics and elastomers. Standard Firm has good strength and elongation making it an excellent reinforcement for water-based cold process and maintenance roof systems.

Standard Firm has a firm but pliable finish. It will provide good conformability on smooth or semi-smooth surfaces. Standard Firm works well when used over smooth or cap sheet surfaces. It has fewer stitches per inch, which allows for better wetability, which requires less brooming. Because it has a firm (starched) finish it will have fewer wrinkles and will lay straighter and smoother during application.

SIZES AVAILABLE

A40F (40" x 324') - 7cpi

PROPERTIES

Weight	2.70 ounce per square yard
Thickness	0.188
Tensile Average	WARP 43.16 lbs. WEFT 55.33 lbs.
Elongation at break	WARP 19.43% WEFT 57.63%
Ball Burst Strength	69.83 lbs.
Trapezoid Tear-Strength Average	WARP 9.85 lbs. WEFT 25.2 lbs.

Data provided here is based on our best knowledge at time of printing and is subject to change. E-las•tek offers coatings to fill or coat ponding areas and to handle difficult substrates. For most current information check our website: www.elastek.com; or contact us at coatings@elastek.com or 877-352-7835.