


## Hazardous Materials Identification System (HMIS)

Health 1 Flammability 0 Reactivity 0 Personal Protection G



### 1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

#### AQUEOUS ROOF MASTIC FORMULATION

PRODUCT CODE: E•LAS•TEK #120 SOLAR TEK EXTREME™

MSDS DATE: 06/01/2004

#### KEY:

#### COMPANY IDENTIFICATION

Structural Elastomeric Products, Inc.  
3700 S. Palo Verde Road  
Tucson, Arizona 85713

#### EMERGENCY TELEPHONE NUMBERS

Health Emergency: 877-352-7835  
Spill Emergency: 877-352-7835

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

No	CAS REG NO	WEIGHT (%)
1 Acrylic polymer	Not Hazardous	44.8 MIN
2 Titanium dioxide	13463-67-7	____
3 Calcium carbonate	1317-65-3	____
4 Fused silica	60676-86-0	____
5 Silicates	Mixture	____
6 Propylene glycol	57-55-6	10.0 MAX
7 Water	7732-18-5	45.0 MAX
8 Ammonia	7664-41-7	00.1 MAX
9 Residual monomer(s)	Not Required	00.1 MAX

NOTE: the |- in the WEIGHT (%) column is used to denote two or more components whose weight percents sum to the total shown by the figure either to the right of, or immediately above the |-.

See Section 8, Exposure Controls / Personal Protection

### 3. HAZARDS IDENTIFICATION

#### PRIMARY ROUTES OF EXPOSURE

- Inhalation
- Skin Contact
- Eye Contact

#### INHALATION

Inhalation of vapor or mist can cause the following:

- Irritation of nose, throat and lungs
- Headache - nausea

#### EYE CONTACT

Material can cause the following:

- Moderate irritation

#### SKIN CONTACT

Prolonged or repeated skin contact can cause the following:

- Irritation, if not promptly washed from skin

#### INGESTION

Consult a physician

NOTES TO PHYSICIAN: Toxicology studies of similar materials have shown the material to be of very low acute toxicity. There is no specific antidote. Treatment of overexposure should be directed at the control of the symptoms and clinical condition.

### 4. FIRST AID MEASURES

#### INHALATION

Move subject to fresh air

#### EYE CONTACT

Flush eyes with a large amount of water for at least 15 minutes. Consult a physician if irritation persists.

#### SKIN CONTACT

Remove contaminated clothing. Wash affected skin areas thoroughly with soap and water. Consult a physician if irritation persists. Wash contaminated clothing thoroughly before reuse. Do not take clothing home to be laundered.

#### INGESTION

If swallowed, give 2 glasses of water to drink. Never give anything by mouth to an unconscious person. Consult a physician.

### 5. FIRE-FIGHTING MEASURES

Flash Point ..... Noncombustible

Auto-ignition Temperature ..... Not Applicable

Lower Explosive Limit ..... Not Applicable

Upper Explosive Limit ..... Not Applicable

#### UNUSUAL HAZARDS

Material can splatter above 100 C/212 F. Dried product can burn.

#### EXTINGUISHING AGENTS

Use extinguishing media appropriate for surrounding fire.

#### PERSONAL PROTECTIVE EQUIPMENT

As in any fire, wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

#### SPECIAL PROCEDURES

Use water spray to cool containers exposed to fire.

### 6. ACCIDENTAL RELEASE MEASURES

#### PERSONAL PROTECTION

Appropriate protective equipment must be worn when handling a spill of this material. See SECTION 8, Exposure Controls/Personal Protection, for recommendations. If exposed to material during clean-up operations, see SECTION 4, First Aid Measures, for actions to follow.

#### PROCEDURES

Keep spectators away. Floor may be slippery; use care to avoid falling. Contain spills immediately with inert materials (e.g. sand, earth). Transfer liquids and solid diking material to separate suitable containers for recovery or disposal.

CAUTION: Keep spills and runoff out of municipal sewers and open bodies of water.

### 7. HANDLING & STORAGE

#### STORAGE CONDITIONS

The minimum recommended storage temperature for this material is 1C/34F. The maximum recommended storage temperature is 60C/140F. Keep from freezing; material may coagulate. Do not store this material near food, feed or drinking water.

#### HANDLING PROCEDURES

Do not handle material near food, feed or drinking water

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### EXPOSURE LIMIT INFORMATION

No	CAS REG NO	WEIGHT (%)
1 Acrylic polymer	Not Hazardous	44.8 MIN
2 Titanium dioxide	13463-67-7	____
3 Calcium carbonate	1317-65-3	____
4 Fused silica	60676-86-0	____
5 Silicates	Mixture	____
6 Propylene glycol	57-55-6	10.0 MAX
7 Water	7732-18-5	45.0 MAX
8 Ammonia	7664-41-7	00.1 MAX
9 Residual monomer(s)	Not Required	00.1 MAX

Comp No	Units	OSHA		ACGIH	
		TWA	STEL	TWA	STEL
1		None	None	None	None
2	mg/m3	10 b	None	10 b	None
3	mg/m3	5 a	None	10 b	None
4	mg/m3	0.1a	None	0.1 a	None
5		None	None	None	None
6	mg/m3	None	None	None	None
7		None	None	None	None
8	ppm	None	35	25	35
9		None	None	None	None

- a Respirable Fraction
- b Total Dust
- c Ceiling

### RESPIRATORY PROTECTION

None required if airborne concentrations are maintained below the exposure limit listed in 'Exposure Limit Information'. A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Up to 1000 ppm organic vapor: Wear a MSHA/NIOSH approved (or equivalent) half-mask, air-purifying respirator.

Above 1000 ppm organic vapor or Unknown: Wear a MSHA/NIOSH approved (or equivalent) self-contained breathing apparatus in the positive pressure mode —OR—

MSHA/NIOSH approved (or equivalent) full-face-piece airline respirator in the positive pressure mode with emergency escape provisions.

Air-purifying respirators should be equipped with an ammonia/methylamine cartridge. Air-purifying respirators should be equipped with MSHA/NIOSH approved (or equivalent) cartridges for protection against organic vapors and filters for protection against dusts and mists.

### EYE PROTECTION

Use chemical splash goggles (ANSI Z87.1 or approved equivalent). Eye protection worn must be compatible with respiratory protection system employed.

### HAND PROTECTION

Chemical-resistant gloves should be worn whenever this material is handled. The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection:

- Nitrile
- Polyvinyl chloride
- Neoprene

Gloves should be removed and replaced immediately if there is any indication of degradation or chemical breakthrough.

Rinse and remove gloves immediately after use. Wash hands with soap and water.

### ENGINEERING CONTROLS (VENTILATION)

Exterior-use product. Use local exhaust ventilation with a minimum capture velocity of 100 ft/min. (0.5 m/sec) at the point of vapor evolution.

### OTHER PROTECTIVE EQUIPMENT

Facilities storing or utilizing this material should be equipped with an eyewash facility.

## 9. PHYSICAL & CHEMICAL PROPERTIES

Appearance	Milky
Color	White to tan
State	Liquid
Odor Characteristic	Ammonia odor
Viscosity	Variable
Specific Gravity (Water = 1)	>1
Vapor Density (Air = 1)	>1
Vapor Pressure	17mm Hg@20°C/68°F water
Melting Point	Variable
Boiling Point	Variable
Solubility in Water	Dilutable
Percent Volatility	45% Maximum
Evaporation Rate (BAC = 1)	< 1

See Section 5, Fire Fighting Measures

## 10. STABILITY AND REACTIVITY

### INSTABILITY

This material is considered stable.

### HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition may yield the following:  
- acrylic monomers

### HAZARDOUS POLYMERIZATION

Product will not undergo polymerization

### INCOMPATIBILITY

There are no known materials that are incompatible with this product.

## 11. TOXICOLOGICAL INFORMATION

### ACUTE DATA

No toxicity data is available for this material.

The information shown in SECTION 3, Hazards Identification, is based on toxicity profiles of similar materials or on the components present in this material.

## 12. ECOLOGICAL INFORMATION

No applicable data

## 13. DISPOSAL CONSIDERATIONS

### PROCEDURE

Incinerate liquid and contaminated solids in accordance with local, state and federal regulations.

## 14. TRANSPORT INFORMATION

US DOT Hazard Class .....NONREGULATED

## 15. REGULATORY INFORMATION

### WORKPLACE CLASSIFICATION

This product is considered non-hazardous under the OSHA Hazard Communication Standard (29CFR 1910.1200).

This product is a 'controlled product' under the Canadian Workplace Hazardous Materials Information System (WHMIS).

### CERCLA INFORMATION (40CFR 302.4)

Releases of this material to air, land or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA), Title III, Section 304.

### WASTE CLASSIFICATION

When a decision is made to discard this mater as supplied, it is classified as RCRA non-hazardous waste.